

MATERIAL SAFETY DATA SHEET

NAME: GILLETTE SHAVING FOAMS (AEROSOLS)

CAS NO: NA

Effective Date: 12/18/02

Rev: 3

A. — IDENTIFICATION

<u>Composition* (1% or greater)</u> Water (7732-18-5) Stearic (57-11-4) or Palmitic (57-10-3) Acids Triethanolamine (102-71-6) Propellant - Isobutane (75-28-5); Propane (74-98-6); Butane (106-97-8) Laureth-23 (9002-92-0) Aloe Vera Gel	<u>%</u>	Formula: Mixture <hr/> Molecular Weight: NA <hr/> Synonyms: Gillette Series: Arctic Ice Extra Conditioning, Clean Skin, Conditioning, Cool Wave Sensitive Skin, Moisturizing, Pacific Light, Protection, Sensitive Skin, Wild Rain Aloe Enriched, Satin Care: Moisturizing, Sensitive Skin,
---	----------	---

B. — PHYSICAL DATA

Boiling Point <u>NA</u> °F <u>NA</u> °C	Melting Point <u>NA</u> °F <u>NA</u> °C	Freezing Point <u>NA</u> °F <u>NA</u> °C
Specific Gravity (H ₂ O=1) <u>~1 (liquid)</u>	Vapor Density (air=1) <u>NA</u>	Vapor Pressure @ _____ °F <u>NA</u> mm Hg
Evaporation (_____ =1) <u>NA</u>	Saturation in Air (by volume@ _____ °F) <u>NA</u>	Autoignition Temperature <u>NA</u> °F <u>NA</u> °C
% Volatiles <u>>80</u>	Solubility in Water <u>Soluble</u>	pH <u>NA</u>

Appearance/Odor White foamy materials with pleasant fragrances.

Flash Point and Test Method(s) Not determined (See Footnotes)

Flammable Limits in Air (% by volume) Lower NA % Upper NA %

C. — REACTIVITY

Stability <input checked="" type="checkbox"/> stable <input type="checkbox"/> unstable	Polymerization <input type="checkbox"/> may occur <input checked="" type="checkbox"/> will not occur
<u>Conditions to Avoid</u> Extreme heat. Avoid spraying toward open flame.	<u>Conditions to Avoid</u> Not applicable
<u>Incompatible Materials</u> Strong oxidizers	<u>Hazardous Decomposition Products</u> Thermal degradation may produce oxides of carbon and nitrogen; hydrocarbons and derivatives.

*** IF MULTIPLE INGREDIENTS, INCLUDE CAS NUMBERS FOR EACH NA=NOT AVAILABLE**

Footnotes

Contains less than 5% hydrocarbon propellant in a water base formula.

D. — HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Propane - 1000 ppm (OSHA/Germany)

Butane - 800 ppm (OSHA/ACGIH); 600 ppm (U.K.); 1000 ppm (Germany)

These levels not anticipated under foreseeable use conditions.

Warning Signals

Not applicable

Routes/Effects of Exposure

1. Inhalation No adverse effects anticipated from normal use.

2. Ingestion No adverse effects anticipated from normal use. If large amount is ingested, nausea and vomiting may occur.

3. Skin
 - a. Contact
No adverse effects anticipated from normal use.

 - b. Absorption
Not anticipated.

4. Eye Contact Minor irritation may occur.

5. Other Not applicable

E. — ENVIRONMENTAL IMPACT

1. Applicable Regulations 49 CFR 172.101 (U.S.)

2. DOT Hazard Class - ORM-D

3. DOT Shipping Name - Consumer Commodity

Environmental Effects

Not applicable

F. — EXPOSURE CONTROL METHODS

Engineering Controls
General ventilation

Eye Protection
None under normal use conditions.

Skin Protection
None under normal use conditions.

Respiratory Protection
None under normal use conditions.

Other
Product is nonhazardous when used as directed.

KEEP OUT OF REACH OF CHILDREN.

G. — WORK PRACTICES

Handling and Storage
CAUTION: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding (120°F). Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Shake can before use. Storage in large quantities (as in a warehouse) should be in a well-ventilated, cool area.

Normal Clean Up
Wipe up with towel, etc., and place in container for disposal. Wash residue with water.

Waste Disposal Methods
Dispose of in accordance with local, state and federal regulations.

H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area

Not applicable

Fire and Explosion Hazard

Less than 5% hydrocarbon propellant in a water base formula. Container may rocket or explode in heat of fire. Hazardous decomposition products may be produced. (Sec. C.).

Extinguishing Media

As for adjacent fire. Dry chemical, foam, carbon dioxide, water fog.

Firefighting Procedures

In fires involving large quantities of product, self-contained breathing apparatus should be used. Fight fire from a distance or protected area. Cool and use caution when handling fire exposed containers.

I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES**Eyes**

Wash eyes with tepid, clear water.

Skin

Not applicable

Inhalation

No adverse effects anticipated from normal use.

Ingestion

Consult physician.

Notes to Physician

If spontaneous vomiting has not occurred, and large amounts have been ingested, the physician may, at their discretion, administer an emetic or mechanically empty the stomach.

Replaces #1693

SSCA-1730-1539 SSCA-2372-1590, SSCA-1622-1184, SSCA-2336-687, SSCA-2334-1658; SSCA-2346-1658;
 SSCA-2288-1285; SSCA-2332-1285; SSCA-1263-1285, SSCA-2333-687, SSCA-2335-1184, SSCA-2342-1184,
 SSCA-1265-1047, SSCA-2289-1539, SSCA-2285-1539

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.